

## Vectra Sealer / Finish

Vectra is a high performance fast curing floor finish for use on all internal resilient floors such as vinyl, rubber and porous composite tiles. Vectra delivers diamond like brilliance and clarity across a wide variety of surfaces. Vectra can be top coated over Plaza stone floor sealer for even more flexible floorcare solutions.

### Features and Benefits

- Low maintenance floor sealer/finish with excellent durability.
- Vectra is a floor sealer/finish with high gloss for low maintenance areas.
- Vectra responds well to spray buff programs, and exhibits excellent durability and off the mop gloss.
- For best results use with machines 900-1500 rpm.
- Coverage 1 litre approx 50-60 square metres.
- Vectra is extremely hard, with excellent adhesion and good resistance to scuffing and black heel marks.
- Vectra is very fast curing reducing the time between recoats.
- Vectra has excellent gloss and clarity ensuring long term floor appearance.

### Product Usage

Directions for Use:

#### APPLICATION

1. Strip old coatings using a JohnsonDiversey stripper according to label directions. Allow floor to dry.
2. Apply one coat of Vectra using a clean mop or applicator.
3. Allow coat to dry for 20-30 minutes depending on drying conditions.
4. Apply 3-4 further coats of Vectra using a clean mop.

#### MAINTENANCE

1. Dust mop or sweep to remove dust or dirt.
2. Clean floor with a JohnsonDiversey cleaner diluted in cold water according to label directions.
3. Maintain the gloss of Vectra using periodic recoating or spray buffing using an approved pad.
4. Wash out all equipment before storage.



Pg 1 of 2

# Vectra

## Sealer / Finish

### BEFORE RECOATING

1. Dust mop or sweep to remove dust or dirt.
2. Deep scrub floor using an approved pad and JohnsonDiversey cleaner diluted in cold water according to label directions.
3. When dry, apply 2-3 coats of Vectra using a clean mop.
4. Allow coats to dry for 20-30 minutes depending on drying conditions.

### First Aid

In case of contact with eyes rinse thoroughly with large quantities of water for at least 15 minutes.

If swallowed do not induce vomiting. Drink milk or water. Seek medical attention.

See Material Safety Data Sheet for further information.

### Approvals

Slip Classification: Class F AS/NZ5 4586:1999  
NZFSA approved C25 (all animal products except dairy)

### 24 HOUR EMERGENCY RESPONSE

**Within New Zealand 0800 CHEMCALL or 0800 243 622**  
**Outside New Zealand 643 353 0199**

JohnsonDiversey New Zealand Limited, 3 Diversey Lane, Papatoetoe, Auckland, New Zealand  
Phone: (09) 278-2119, Freephone: 0800 803 615  
Website: [www.johnsondiversey.co.nz](http://www.johnsondiversey.co.nz), E-mail: [customerservices.jdnz@johnsondiversey.com](mailto:customerservices.jdnz@johnsondiversey.com)

Pg 2 of 2